

Interior Vinyl Acoustic Flat Finish

Architectural Coating - Premium Plus

Description

A high-hiding, non-bridging premium plus vinyl flat finish for interior acoustical ceilings. Designed to preserve existing sound deadening qualities. Not recommended for wall surfaces.

Recommended Uses

New or previously painted acoustic tile or spray applied acoustic ceilings.

Colors

White and Off-White

Packaging

One and five gallon containers

Finish

Flat, sheen @ 60° = 2.6 – 3.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Primer

Water and smoke damage must be primed with 4200 Terminator II.

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

Drying Time

Touch: 30 minutes
Recoat: 4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 5.2 Dry = 1.5

Thinning

Use at package consistency. If thinning is required, use water sparingly (1/2 pint of water per gallon).

Composition

Titanium Dioxide	3.4%
Extenders	38.5%
TOTAL PIGMENT	42.0%

Vinyl Acrylic	3.9%
Additives	7.7%
Water	46.4%
TOTAL VEHICLE	58.0%

Weights & Measurements +/-3.0%

Solids by Volume:	29.0%
Solids by Weight:	47.0%
VOC:	31 g/l
Weight Per Gal:	11.3 lbs.
Viscosity:	94 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009
-Low Emitting Materials

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 06.16