Acriglo Velvasheen (formerly 6200 Carefree Earth Coat)

1750

Interior/Exterior Zero* VOC 100% Acrylic Enamel Finish

Architectural Coating - Premium

MANUFACTURED USING 100% SOLAR ENERGY

Description

Acriglo 1750 Velvasheen is a premium zero* VOC 100% acrylic for interior and exterior surfaces. This product provides good block resistance, durability, adhesion and mildew resistance. Low odor makes Acriglo Velvasheen suitable for institutional, commercial and residential applications. **NOTE:** This product contains ingredients which resist the growth of mircrobes on the surface of the paint film.

Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

Colors

White and custom colors to order.
Bases: P & D

Packaging

One and five gallon containers

Finish

Velvasheen, sheen @ 60° = 7.0 – 9.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi Build Sealer
Drywall (Existing):	4000 Uniprime
Concrete/Masonry:	4600 Uniprime II
Wood (Exterior):	4200 Terminator II
Wood (Interior):	4000 Uniprime
Metal Non-Galvanized:	8600 Polytec Primer
	9600 Protec Metal Prime
Metal Galvanized:	8600 Polytec Primer
	4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch:	2 hours
Recoat:	4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 3.3 Dry = 1.2

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	17.7%
Extenders	21.3%
TOTAL PIGMENT	**39.0%**
Resin	16.0%
Additives	5.6%
Water	39.4%
TOTAL VEHICLE	**61.0%**

Weights & Measurements +/-3.0%

Solids by Volume:	36.8%
Solids by Weight:	52.1%
VOC:	<2 g/l
Weight Per Gal:	11.1 lbs.
Viscosity:	100 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings
LEED - complies with LEED 2009 and LEEDv4
CDPH Section 01350 - Standard Method V1.2, 2017
MPI - #144

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 09.22

Vista Paint Corporation | 2020 E. Orangethorpe Ave, Fullerton CA 92831
www.vistapaint.com

1750 Acriglo Velvasheen Interior/Exterior Zero* VOC 100% Acrylic Enamel Finish