

### Description

Acriglo is a premium low odor, zero\* VOC, acrylic co-polymer interior flat finish. Exceptional hide and touch-up with superior adhesion. Acriglo is resistant to scuffing, staining and abrasion. Excellent for use in hospitals, hotels/motels, schools, office, homes and occupied areas with minimal disruption. Dries quickly to a tough, durable and washable finish. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

### Recommended Uses

Interior drywall, plaster, masonry, concrete and wood.

### Colors

White and custom colors.  
Bases: A, D and P

### Packaging

One and five gallon containers

### Finish

Flat, sheen @ 85° = 1.0 - 3.0%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Smooth Wood and glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primers

Drywall / Concrete /  
Plaster: 7001 Acriglo Interior Primer  
Wood: 7001 Acriglo Interior Primer

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch: 45 minutes  
Recoat: 6 hours

### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 3.0      Dry = 1.2

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	12.5%
Extenders	28.3%
<b>TOTAL PIGMENT</b>	<b>40.8%</b>
Latex Resin	14.5%
Additives	3.5%
Water	41.2%
<b>TOTAL VEHICLE</b>	<b>59.2%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	41.1%
Solids by Weight:	57.4%
VOC:	<1 g/l
Weight Per Gal:	11.5 lbs.
Viscosity:	96 - 102 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009  
-Low Emitting Materials

**MPI** - #143

**EPA Test Method 24** - yes

**CDPH Section 01350** - tested and passed

\*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.