

### Interior/Exterior Primer/Sealer/Stain Killer

Architectural Coating - Premium Plus

#### Description

A stain blocking, multi-purpose acrylic primer for interior and exterior use. Terminator II has excellent adhesion on a variety of substrates and can be applied on most architectural surfaces. On exterior wood, Terminator II will provide excellent "grain crack resistance" and flexibility needed for the durability of exterior wood surfaces. On redwood and cedar, Terminator II exhibits excellent tannin stain resistance. Terminator II has excellent efflorescent and alkaline resistance that makes this product an excellent choice for stucco and masonry substrates.

#### Recommended Uses

Terminator II has a variety of adhesion properties for interior / exterior wood, galvanized metal, steel, aged alkyd paint, stucco, tilt-ups and masonry. Terminator II will also block most household stains.

#### Colors

White

#### Packaging

One and five gallon containers

#### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings. Cedar, redwood and other woods prone to extractive bleeding may require additional coats. Knots and stains should be sealed with two (2) coats of 4200 Terminator II.

**Passivation coatings applied to galvanized metal must be removed prior to priming. Newly galvanized substrates should be tested for chromates. Refer to SSPC SP-16 for proper testing and surface preparation.**

#### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### Drying Time

Touch: 2 hours  
Recoat: 4 hours (at normal conditions)

#### Coverage

Up to 375 square feet per gallon, depending on porosity and texture of the surface.

#### Mil Thickness

Wet = 3.9      Dry = 1.9

#### Thinning

Use at package consistency. If thinning is required, use water sparingly.

#### Composition

Titanium Dioxide	12.8%
Extenders	16.6%
<b>TOTAL PIGMENT</b>	<b>29.4%</b>

Resin	22.2%
Additives	4.8%
Water	43.6%
<b>TOTAL VEHICLE</b>	<b>70.6%</b>

#### Weights & Measurements +/-3.0%

Solids by Volume:	39.0%
Solids by Weight:	54.0%
VOC:	47 g/l
Weight Per Gal:	10.9 lbs.
Viscosity:	92 - 96 KU

#### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009 and LEEDv4 -Low Emitting Materials

**CDPH Section 01350** - tested and passed

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.