

Interior/Exterior 100% Acrylic Finish
Architectural Coating - Premium Plus

Description

Carefree Flat is a premium plus 100% acrylic interior/exterior matte flat finish which provides superior washability and scrubability. This premium flat exhibits excellent stain and dirt resistance, burnish resistance, hide, color retention and adhesion. Use of Carefree Flat resolves the problem of scuffing and burnishing, particularly in dark colors. Carefree Flat can be applied over new or previously painted drywall, plaster, stucco and wood. Carefree Flat has excellent application properties and spatter resistance. Excellent for use on commercial, residential, institutional or custom painting interior and exterior projects. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Properly primed interior/exterior drywall, plaster, concrete, masonry, wood and metal.

Colors

White, stock colors and custom colors to order.
Bases: A, D, H and P

Packaging

One and five gallon containers

Finish

Flat, sheen @ 85° = 2.5 - 3.5%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi-Build Sealer 8000 Carefree Prime-ZALL
Drywall (Existing):	4000 Uniprime 8000 Carefree Prime-ZALL
Concrete/Masonry:	4600 Uniprime II 8000 Carefree Prime-ZALL
Wood (Interior):	6600 AquaLac Undercoat 8000 Carefree Prime-ZALL
Wood (Exterior):	4000 Uniprime 8000 Carefree Prime-ZALL
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Prime
Metal Galvanized:	8600 Polytec Primer 4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 1 hour
Recoat: 4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 3.8 Dry = 1.7

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	19.6%
Extenders	14.5%
TOTAL PIGMENT	34.1%
Acrylic Resin	12.4%
Additives	10.8%
Water	42.7%
TOTAL VEHICLE	65.9%

Weights & Measurements +/-3.0%

Solids by Volume:	39.3%
Solids by Weight:	55.3%
VOC:	22 g/l
Weight Per Gal:	11.48 lbs.
Viscosity:	98 - 102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4
-Low Emitting Materials

CDPH Section 01350 - tested and passed
MPI - #53

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 08.18