

Description

Carefree Velva Sheen is a premium plus 100% acrylic low sheen interior/exterior finish, which provides block resistance with superior washability, scrubbability and exterior durability. This velvet finish exhibits exceptional stain and dirt resistance with good hide and adhesion. Carefree Velva Sheen can be applied on drywall, plaster, stucco and wood. Excellent for use on commercial, residential, institutional or custom painting projects. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Properly primed drywall, plaster, stucco, concrete, masonry, wood and metal.

Colors

White, stock and custom colors to order.
Bases: A, D, H and P

Packaging

One and five gallon containers

Finish

Low sheen, sheen @ 60° = 9.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi-Build Sealer 8000 Carefree Prime-ZALL
Drywall (Existing):	4000 Uniprime 8000 Carefree Prime-ZALL
Concrete/Masonry:	4600 Uniprime II 8000 Carefree Prime-ZALL
Wood (Exterior):	4200 Terminator II 8000 Carefree Prime-ZALL
Wood (Interior):	6600 AquaLac Undercoat 8000 Carefree Prime-ZALL
Ferrous Metal:	9600 Protec Metal Prime White 9610 Protec Metal Prime Red Oxide
Non-Ferrous Metal	4800 Metal Pro Primer White 4810 Metal Pro Primer Red Oxide

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%.

Clean tools and equipment with soap and water.

Drying Time

Touch: 1 hour
Recoat: 4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.0 Dry = 1.7

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	22.7%
Extenders	18.0%
TOTAL PIGMENT	40.7%

Acrylic Resin	19.9%
Additives	4.8%
Water	34.6%
TOTAL VEHICLE	59.3%

Weights & Measurements +/-3.0%

Solids by Volume:	41%
Solids by Weight:	55%
VOC:	47 g/l
Weight Per Gal:	11.3 lbs.
Viscosity:	92 - 96 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4 -Low Emitting Materials

CDPH Section 01350 - tested and passed
MPI - #44, #138

DISCLAIMER: Our best effort to provide the most accurate technical information is made. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 06.16