

Description

Carefree Eggshell is a premium plus 100% acrylic eggshell enamel for interior and exterior surfaces. This top-of-the-line enamel provides block resistance with excellent scrubbability and durability. Carefree Eggshell finish exhibits exceptional stain and dirt resistance with excellent hide and adhesion. Carefree can be used in areas where oil based products were previously required. Excellent choice for use on commercial, residential, institutional or custom painting projects. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

Colors

White, stock and custom colors to order.

Bases: A, D, H and P

Packaging

Quarts, one and five gallon containers

Finish

Eggshell, sheen @ 60° = 14.0 - 18.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi-Build Sealer 8000 Carefree Prime-ZALL
Drywall (Existing):	4000 Uniprime 8000 Carefree Prime-ZALL
Concrete/Masonry:	4600 Uniprime II 8000 Carefree Prime-ZALL 8600 Polytec Primer
Wood (Exterior):	4200 Terminator II 8000 Carefree Prime-ZALL 8600 Polytec Primer
Wood (Interior):	6600 AquaLac Undercoat 8000 Carefree Prime-ZALL 8600 Polytec Primer
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Prime
Metal Galvanized:	8600 Polytec Primer
Aluminum:	4800 Metal Pro Primer 8600 Polytec Primer

Drying Time

Touch: 1 hour
Recoat: 4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.3 Dry = 1.5

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	17.2%
Extenders	10.4%
TOTAL PIGMENT	27.6%
Acrylic Resin	21.3%
Additives	8.5%
Water	42.6%
TOTAL VEHICLE	72.4%

Weights & Measurements +/-3.0%

Solids by Volume:	36.0%
Solids by Weight:	50.3%
VOC:	43 g/l
Weight Per Gal:	10.8 lbs.
Viscosity:	96 - 100 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4 -Low Emitting Materials

CDPH Section 01350 - tested and passed
MPI - #15, #52, #139, #151, #161

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.