

Description

Carefree Semi-Gloss is a premium plus 100% acrylic enamel for interior and exterior surfaces. This top-of-the-line enamel provides block resistance with excellent scrubability and durability and is formulated to withstand moderate to severe weather conditions. Excellent choice for use in food and beverage areas, restrooms, doors, trim and exterior substrates where a superior semi-gloss finish is desired. **NOT FOR USE ON FOOD CONTACT SURFACES.** Carefree can be used in areas where oil based products were previously required. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

Colors

White, stock and custom colors to order.
Bases: A, D, P & H

Packaging

Quarts, one and five gallon containers

Finish

Semi-Gloss, sheen @ 60° = 60.0 - 64.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi-Build Sealer 8000 Carefree Prime-ZALL
Drywall (Existing):	4000 Uniprime 8000 Carefree Prime-ZALL
Concrete/Masonry:	4600 Uniprime II 8000 Carefree Prime-ZALL
Wood (Exterior):	4000 Uniprime 8000 Carefree Prime-ZALL
Wood (Interior):	6600 AquaLac Undercoat 8000 Carefree Prime-ZALL
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Primer
Metal Galvanized:	8600 Polytec Primer 4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 2 hours
Recoat: 8 hours

Coverage

Up to 375 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.2 Dry = 1.4

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	20.3%
Extenders	1.4%
TOTAL PIGMENT	21.7%
Acrylic Resin	19.5%
Additives	4.6%
Water	54.2%
TOTAL VEHICLE	78.3%

Weights & Measurements +/-3.0%

Solids by Volume:	35.0%
Solids by Weight:	47.7%
VOC:	44 g/l
Weight Per Gal:	10.7 lbs.
Viscosity:	96 - 100 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009 and LEEDv4 -Low Emitting Materials

CDPH Section 01350 - tested and passed

MPI - #11, #54, #54 X-Green, #141, #153, #163 and #311

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 08.18