

## Interior/Exterior Vinyl-Acrylic Flat Finish Architectural Coating - Premium

### Description

Duraglide is a premium vinyl-acrylic exterior and interior flat. This product has excellent touch-up, outstanding hide and good washability characteristics. Duraglide offers good color retention & adhesion and is designed for use on all interior drywall and exterior / interior masonry surfaces.

### Recommended Uses

Properly primed drywall, concrete, masonry, stucco, plaster and metal. **NOT recommended for use on exterior wood.**

### Colors

White and stock colors. Custom colors to order.  
Bases: White, P, D and H

### Packaging

Quart, one and five gallon containers

### Finish

Flat, sheen @ 85° = 1.8 – 2.2%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primer

Drywall (New):	1100 Hi Build Sealer
Drywall (Existing):	4000 Uniprime
Concrete/Masonry:	4600 Uniprime II
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Primer
Metal Galvanized:	8600 Polytec Primer 4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch: 1 hour  
Recoat: 4 hours

### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 3.8      Dry = 1.6

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	15.3%
Extenders	31.1%
<b>TOTAL PIGMENT</b>	<b>46.4%</b>

Vinyl Acrylic Resin	13.8%
Additives	4.6%
Water	35.2%
<b>TOTAL VEHICLE</b>	<b>53.6%</b>

### Weights & Measurements +/-3.0%

Solids by Volume:	41.8%
Solids by Weight:	58.7%
VOC:	47 g/l
Weight Per Gal:	11.8 lbs.
Viscosity:	98 - 102 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings  
**LEED** - complies with LEED 2009  
-Low Emitting Materials  
**MPI** - #53

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 08.18