

Exterior 100% Acrylic Flat Finish
Architectural Coating - Premium

Description

A premium 100% acrylic solid-bodied stain and finish for exterior use. Acribond is for use on all wood, masonry and previously painted surfaces. Acribond provides a durable matte flat finish with excellent color retention and mildew resistance.

Recommended Uses

New or previously painted wood. Properly primed concrete, stucco, masonry and metal.

Colors

White, stock and custom colors to order.
Bases: A, D, H and P

Packaging

Quart, one and five gallon containers

Finish

Flat, sheen @ 85° = 1.2 – 1.6%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming. Woods prone to extractive bleeding require a stain blocking primer.

Primer

Concrete/Masonry:	4600 Uniprime II
Cedar/Redwood:	4000 Uniprime 8000 Carefree Prime-ZALL
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Primer
Metal Galvanized:	8600 Polytec Primer 4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%.
Clean tools and equipment with soap and water.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Drying Time

Touch:	1 hour
Recoat:	4 - 6 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.0	Dry = 1.6
-----------	-----------

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	13.5%
Extenders	28.1%
TOTAL PIGMENT	41.6%

Acrylic Resin	14.4%
Additives	3.9%
Water	40.1%
TOTAL VEHICLE	58.4%

Weights & Measurements +/-3.0%

Solids by Volume:	40.8%
Solids by Weight:	58.0%
VOC:	48 g/l
Weight Per Gal:	11.9 lbs.
Viscosity:	98 - 102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings
MPI - #10, #16

Revised 08.18