

Description

Production AquaLac is a quality waterbased zero* VOC acrylic quick dry primer which offers excellent sanding properties and minimum grain raise. Designed for new or refinished projects over wood, drywall, paneling, hardboard and many other interior surfaces. This product offers excellent adhesion and enamel hold out.

Recommended Uses

Drywall, hardboard, wood surfaces, cabinets or other interior surfaces.

Colors

White

Packaging

Five gallon containers

Finish

Flat

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Application

Spray only. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Sand After: 1 - 2 hours

Topcoat After: 2 hours

Coverage

Up to 350 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 5.3 Dry = 2.1

Thinning

If thinning is required, use water sparingly.

Composition

Titanium Dioxide	9.1%
Extenders	26.8%
TOTAL PIGMENT	35.9%

Acrylic Resin	16.8%
Solvents & Additives	5.8%
Water	41.5%
TOTAL VEHICLE	64.1%

Weights & Measurements +/-3.0%

Solids by Volume:	39.7%
Solids by Weight:	54.4%
VOC:	<5 g/l
Weight Per Gal:	11.0 lbs.
Viscosity:	78 - 82 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009

-Low Emitting Materials

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.