



Description

1200 Coverall Low Sheen is a quality interior water-based production enamel which provides excellent scrubability and washability. 1200 Coverall Low Sheen can be applied over new or previously painted drywall, plaster and wood surfaces. For use on commercial, institutional and property management projects.

Recommended Uses

Previously painted or properly primed interior drywall, plaster, concrete, masonry and wood. Not recommended for wood cabinets or doors as blocking may occur.

Colors

White and custom pastel colors to order.
Bases: White & P

Packaging

One and five gallon containers

Finish

Low sheen, sheen @ 60° = 7.8 – 8.2%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

- Drywall (New): 155 Seal Kote
- Drywall (Existing): 4000 Uniprime
- Concrete/Masonry: 4600 Uniprime II
- Wood: 188 Acrylic Primer
- 4200 Terminator II
- 6600 AquaLac

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

- Touch: 2 hours
- Recoat: 4 - 6 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

- Wet = 3.4
- Dry = 1.3

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	14.1%
Extenders	18.3%
TOTAL PIGMENT	32.4%
Vinyl Acrylic Resin	18.3%
Additives	5.0%
Water	44.3%
TOTAL VEHICLE	67.6%

Weights & Measurements +/-3.0%

Solids by Volume:	37.7%
Solids by Weight:	52.8%
VOC:	41 g/l
Weight Per Gal:	11.0 lbs.
Viscosity:	96 - 100 KU

Conformance

- SCAQMD** - complies with Rule 1113, Architectural Coatings
- LEED** - complies with LEED 2009 -Low Emitting Materials

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.