

Description

A quality zero* VOC high hide latex flat designed to block out graffiti on masonry surfaces.

Recommended Uses

Masonry (interior / exterior) and metal surfaces.

Colors

White and factory-tint.

Packaging

Five gallon container

Finish

Flat

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Recoat: 2 hours

Coverage

Up to 525 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 2.8 Dry = 1.0

Thinning

Use at package consistency. If thinning is required, use water sparingly (1/2 gallon water per 5-gallon container).

Composition

Titanium Dioxide	5.7%
Extenders	37.8%
TOTAL PIGMENT	43.5%

Vinyl Acrylic Resin	7.3%
Additives	4.5%
Water	44.2%
TOTAL VEHICLE	56.0%

Weights & Measurements +/-3.0%

Solids by Volume:	35.5%
Solids by Weight:	53.2%
VOC:	<2 g/l
Weight Per Gal:	11.5 lbs.
Viscosity:	85 - 92 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009
-Low Emitting Materials

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliance Coatings category.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.