

Description

A quality interior vinyl acrylic flat finish that provides excellent hide, coupled with excellent touch-up characteristics. Ideal for commercial and residential applications.

Recommended Uses

Previously painted or properly primed interior drywall, plaster, concrete and masonry.

Colors

Stock Colors: 00 White
23 Swiss Coffee
32 Shell White
33 Off White
60 Indian White

Custom pastel colors to order.

Packaging

Five gallon containers

Finish

Flat, sheen @ 85° = 0.8 – 1.5%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming. Smoke and water stains should be sealed with 4200 Terminator II.

Primer

Drywall: 155 Seal Kote
1100 Hi-Build PVA Sealer
Plaster/Concrete/
Masonry: 4600 Uniprime II

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 1 hour
Recoat: 2 hours

Coverage

Up to 500 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 3.1 Dry = 1.2

Thinning

May be thinned up to 1 1/2 gallons of water per five (5) gallon container.

Composition

Titanium Dioxide	9.6%
Extenders	38.4%
TOTAL PIGMENT	48.0%

Vinyl Acrylic Resin	8.8%
Additives	6.8%
Water	36.4%
TOTAL VEHICLE	52.0%

Weights & Measurements +/-3.0%

Solids by Volume:	39.2%
Solids by Weight:	57.1%
VOC:	44 g/l
Weight Per Gal:	12.1 lbs.
Viscosity:	140 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings
LEED - complies with LEED 2009
-Low Emitting Materials

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 06.16