

Zero* V.O.C. Interior Water-Based Prep Coat

Architectural Coating - Specialty

Description

A specialty water-based zero* VOC primer-surfacer for interior use on new drywall. Provides a uniform surface porosity between drywall and joints. Uniprep fills and levels uneven new drywall.

Recommended Uses

New drywall construction and plaster.

Colors

White

Packaging

Five gallon containers

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Not recommended for use over previously painted surfaces. Joint compound must be thoroughly dry and sanded smooth.

Application

Spray only. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

Drying Time

Dry to Touch: 1 hour

Coverage

Up to 200 square feet per gallon, depending on porosity and texture of the surface at 3.0 mil dry.

Mil Thickness

Wet = 9.0 Dry = 3.0

Thinning

No thinning required. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	2.24%
Extenders	39.44%
TOTAL PIGMENT	41.68%
Vinyl Acrylic Resin	4.96%
Solvents	0.50%
Additives	4.53%
Water	48.33%
TOTAL VEHICLE	58.32%

Weights & Measurements +/-3.0%

Solids by Volume:	33.5%
Solids by Weight:	53.0%
VOC:	<1 g/l
Weight Per Gal:	11.38 lbs.
Viscosity:	94 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings

LEED - complies with LEED 2009
-Low Emitting Materials

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Revised 06.16