

Interior / Exterior Acrylic Low Sheen Finish

Architectural Coating - Quality

### Description

MB30 is an acrylic low sheen for interior and exterior surfaces. MB30 is designed with good exterior durability and fade resistance for modular structures or other areas where a quality, satin product is desired.

### Recommended Uses

Wood, plywood, drywall and masonry surfaces.

### Colors

White, pastel and deep colors.

### Packaging

Five gallon containers

### Finish

Satin, sheen @ 60° = 7.4%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion.

### Primer

Masonry:	4600 Uniprime II
Wood:	4000 Unprime
Metal:	4800 Metal Pro Primer

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

### Drying Time

Recoat: 4 hours

### Coverage

Up to 350 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 3.7 - 5.0      Dry = 1.5 - 2.0

### Thinning

If necessary, thin with water sparingly.

### Composition

<b>TOTAL PIGMENT</b>	<b>33.6%</b>
Titanium Dioxide	13.3%
Extenders	20.3%

<b>TOTAL VEHICLE</b>	<b>66.4%</b>
Resin	19.2%
Additives	4.2%
Water	43.0%

Weights & Measurements +/-3.0%

Solids by Volume:	40.3%
Solids by Weight:	55.3%
VOC:	45 g/l
Weight Per Gal:	11.0 lbs.
Viscosity:	94 - 98 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings

**LEED** - complies with LEED 2009  
-Low Emitting Materials

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.